

SINGLE STAGE COMPRESSOR TEST UNIT F860



Year 1 study

Features

- Allows Investigation of a Single Stage Compressor at a Range of Delivery Pressures.
- · Safe and Suitable For Student Operation.
- Instrumentation Allows Detailed Analysis of Compressor Performance.
- Optional Computerised Data Acquisition Upgrade

Description

A bench mounted unit with a belt driven reciprocating air compressor. The drive motor is mounted in bearings and allows the torque required to drive the compressor to be measured using an integral balance. With the measured torque and motor speed the shaft power required to drive the compressor may be determined. Compressor speed is measured through the fixed pulley ratio between the drive motor and compressor.

Panel mounted meters allow the motor electrical input to be compared to the measured shaft power.

The intake air passes through an orifice for flow measurement to a vessel that reduces intake pulsations and allows various intake conditions to be established. The intake and delivery pressures are indicated on gauges and all of the relevant system temperatures are recorded by thermocouple sensors connected to multiple selector switches and a digital temperature indicator.

The flow measurement orifice is connected to a panel mounted manometer to allow differential pressure measurement. Air is delivered to a receiver fitted with a high pressure cut out and relief valve for operator safety. A throttle valve allows discharge pressure to be controlled and adjusted.

Related laws



- Thermodynamics
- Energy Conservation
- Mechanical Engineering
- · Plant and Process Engineering
- · Automotive Engineering
- Fluid Mechanics

Learning capabilities

- Investigation of Variation in Air Flow Rate With Compressor Pressure Ratio.
- Investigation of Variation in Volumetric Efficiency with Compressor Pressure Ratio.
- Investigation Of Variation Of Isothermal Efficiency With Compressor Pressure Ratio.
- Investigation Of The Compressor Performance Relative To Electrical Power, Shaft Power, And Heat Loss.

Technical Specification

- Two Cylinder Compressor
- Compressor Dimensions:
- Bore: 60mmStroke: 24mm
- Swept Volume per revolution: 0.135 Litres
- Motor Torque Arm Radius: 112mm

What's in the Box?

- 1 x F860
- Country Specific Power Lead
- Instruction manual
- · Packing List
- Test Sheet
- Wiring Diagram

You might also like

• F865

Weights & Dimensions

Weight: 80 kgLength: 940mmWidth: 600mm

Height: 1140mm

Essential Services

- 220-240 Volts, Single Phase, 50Hz/60Hz (With earth/ground).
- Line current up to 10A at 230v.
- 110-120 Volts, Single Phase, 60Hz (With earth/ground).
- Line current up to 20A at 110v.

Ordering information

To order this product, please call PA Hilton quoting the following codes:

F860/230 F860/115 F860/230/FC F860/115/FC

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure.

Copyright © 2018 P.A. Hilton Limited. All rights reserved. This technical leaflet, its contents and/or layout may not be modified

and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of P. A. Hilton Limited. Hi-Tech Education is a registered trade mark of P. A. Hilton Limited.

COUNTRY OF ORIGIN - UK WARRANTY PERIOD - 2 YEARS